Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-3 (cancelled).

Claim 4 (previously presented). A process for dyeing or printing textile fibre materials, comprising applying a dyeing preparation in the form of an aqueous dye bath or printing paste to the textile fibre material wherein the dyeing preparation comprises a gloss pigment A or B wherein gloss pigment A has the following layer structure: SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/S

B(a) a core consisting essentially of one or more silicon oxides wherein the molar ratio of oxygen to silicon is on average from 0.03 to 0.95.

Claim 5 (original). A process according to claim 4, wherein the gloss pigment A has the following layer structure: SiO₂/SiO_x/SiO_y/SiO_y/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/SiO₂/TiO₂, wherein x is from 0.03 to 0.95 and y is from 0.95 to 1.8, the core is a platelet having an average diameter of from 1 to 50 µm and a thickness of from 20 to 500 nm, the thickness of the SiO_x layer is from 5 to 200 nm, the thickness of the SiO_y or SiO₂ layer is from 1 to 200 nm, and the thickness of the TiO₂ layer is from 1 to 180 nm.

Claims 6-20 (cancelled).